Fabriksvangen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

K-VLBP CAM & GROOVE TYPE B

CAM & GROOVE Polypropylene External Thread:

Quick-connect coupling featuring a female adapter and external thread, designed for efficient fluid transfer. Made from durable Polypropylene plastic, it offers excellent chemical resistance and is lightweight, making it ideal for various applications.

Temperature range:

- -10°C – +70°C

Inch	**½" – 2"**	**2 ½"**	**3"**	**4"**	**5"**	**6"**	**8"**
Scale	**Bar / Psi**	**Bar / Psi**	**Bar / Psi**	**Bar / Psi**	**Bar / Psi**	**Bar / Psi**	**Bar / Psi**
Working Pressure	7 / 100	4 / 50	4 / 50	4 / 50	-	-	-

Type	**Material**	**Description**	**Item Number**	**EAN-number**
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 1/2"	K-VLBP013A	5 714397 005047
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 3/4"	K-VLBP019A	5 714397 005122
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 1"	K-VLBP025A	5 714397 005207
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 1-1/4"	K-VLBP032A	5 714397 005276
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 1-1/2"	K-VLBP038A	5 714397 005351
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 2"	K-VLBP050A	5 714397 005443
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 3"	K-VLBP075A	5 714397 005580
Type B	Polypropylene	CAM & GROOVE TYPE B PP D. 4"	K-VLBP100A	5 714397 005665

** All technical specifications apply to a temperature of 23° C ± 2° C*