



Fabriksvngen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

K-VLCA CAM & GROOVE TYPE C

CAM & GROOVE Aluminum Hose Tail:

Quick-connect coupling featuring a female adapter and hose tail, designed for efficient fluid transfer. Made from robust aluminum, it provides high durability and strength while remaining lightweight, making it ideal for various applications.

Temperature range:

➤ -10°C – +100°C



Inch	1/2" – 2"	2 1/2"	3"	4"	5"	6"	8"
Scale	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi
Working Pressure	18 / 250	11 / 150	9 / 125	7 / 100	5 / 75	5 / 75	3 / 50

Type	Material	Description	Item Number	EAN-number
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 1/2"	K-VLCA013A	5 714397 005849
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 3/4"	K-VLCA019A	5 714397 005924
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 1"	K-VLCA025A	5 714397 006006
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 1-1/4"	K-VLCA032A	5 714397 006068
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 1-1/2"	K-VLCA038A	5 714397 006143
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 2"	K-VLCA050A	5 714397 006211
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 2-1/2"	K-VLCA063A	5 714397 006287
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 3"	K-VLCA075A	5 714397 006334
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 4"	K-VLCA100A	5 714397 006402
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 5"	K-VLCA125A	5 714397 006488
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 6"	K-VLCA150A	5 714397 006518
Type C	Aluminum	CAM & GROOVE TYPE C ALU D. 8"	K-VLCA200A	5 714397 006558

* All technical specifications apply to a temperature of 23° C ± 2° C