



Fabriksvngen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

K-VLFP CAM & GROOVE TYPE F

CAM & GROOVE Polypropylene External Thread:

Quick-connect coupling featuring a male adapter and external thread, designed for efficient fluid transfer. Made from durable Polypropylene plastic, it offers excellent chemical resistance and is lightweight, making it ideal for various applications.



Temperature range:

➤ -10°C – +70°C

Inch	½" – 2"	2 ½"	3"	4"	5"	6"	8"
Scale	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi
Working Pressure	7 / 100	4 / 50	4 / 50	4 / 50	-	-	-

Type	Material	Description	Item Number	EAN-number
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 1/2"	K-VLFP013A	5 714397 009939
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 3/4"	K-VLFP019A	5 714397 010027
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 1"	K-VLFP025A	5 714397 010102
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 1-1/4"	K-VLFP032A	5 714397 010164
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 1-1/2"	K-VLFP038A	5 714397 010245
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 2"	K-VLFP050A	5 714397 010324
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 3"	K-VLFP075A	5 714397 010461
Type F	Polypropylene	CAM & GROOVE TYPE F PP D. 4"	K-VLFP100A	5 714397 010546

* All technical specifications apply to a temperature of 23° C ± 2° C